NORTH CAROLINA OFFICIAL WAIVER OF MINIMUM REQUIREMENTS FOR THE CONTROL OF SUBTERRANEAN TERMITES IN EXISTING STRUCTURES

Property Owner: Patricia and Glenn Holloway	Agent:
Address: 2214 Fairview Road	Address:
City: Raleigh, NC 27608	City:
Location of Property, if different from above: Same	Date of Contract: 09/18/2026

Type of Construction	Basement:	Crawl-Space:	Slab:	Combination:
	☐	☑	☐	☐

Before signing this form you should read and understand each of the treatment specifications indicated below. These specifications are based on the minimum requirements of the N.C. Structural Pest Control Committee.

The items checked below apply to the structure to be treated and **will not be performed** in treating the property listed above. Any item checked below must be explained on the right adjacent to the item checked on the left.

I. Mechanical Alterations/Sanitation:

Explanation and location of item(s) waived :

☐ A. Provide access openings to permit inspection of all basement and crawl-space areas.

☐ B. Remove all wood and cellulose materials , such as stumps, form boards and construction debris, contacting soil in all crawl-space areas.

☐ C. Provide required clearance between soil and wood floor joists, girders and subsills.

☐ D. Remove all visible tubes or tunnels on the foundation and other structures below the sill line.

☐ E. Remove all wooden contacts between the building and soil both outside and inside except those which are pressure treated.

II. Foundation Treatment:

☐ F. Drill and treat with a termiticide all voids in multiple masonry walls within 4 feet of any evidence of termites.

☐ G. Drill and treat with a termiticide all voids in multiple masonry pillars, pilasters, chimneys, and step buttresses within 4 feet of any evidence of termites.

☐ H. Drill and treat with a termiticide voids in porch walls.

III. Slab Treatment:

☐ I. Drill and treat all concrete slab porches as required.

☑ J. Where concrete slabs other than porches, such as walkways, carports and patios, prevent trenching soil adjacent to foundation elements, drill slab and treat soil beneath slab.

Left side flagstone patio (14 ft of foundation) not drilled; soil below untreated. Owner declined.

☐ K. Treat soil with a termiticide beneath floor slabs, such as garages, storage rooms and interior floor slabs.

IV. Soil Treatment:

☐ L. Treat soil with a termiticide adjacent to all foundation elements, pipes and other utility conduits both inside and outside the foundation wall. (If slabs adjacent to the foundation wall prevent trenching, see “Slab Treatment J.” above.)

☐ M. Trench and treat soil with a termiticide to a depth below and under the edge of stucco on wood or similar type material.

V. Service Agreement Information:

This treatment is ☑ is not ☐ covered by a service agreement (one must be checked). If a service agreement is to be issued, a copy is attached to these specifications.

Company:	License No.:	Signature of Licensee or Company Representative:
Oak City Termite & Pest	2184 PW	James Whitaker

PROPERTY OWNER/AGENT: DO NOT SIGN THIS FORM IF YOU DO NOT UNDERSTAND IT OR IF YOU HAVE ANY QUESTIONS REGARDING THE QUALITY OR EXTENT OF TREATMENT TO BE PERFORMED. DO NOT SIGN A BLANK FORM.

Signature of Owner / Agent:	Date:
Patricia Holloway	09/18/2026

Form No. 5. (Revised Effective March 1, 1999)